Commercial Fishing Vessel Safety Exam Checklist Documented Vessels < 40', within Coastal Waters

| Vessel Name: | Number: | | |
|-------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------|--|
| BRIDGE & DOCUMENTS | | | |
| 33 CFR 173 46 CFR 67 | Registration/Documents/Markings: Certificate of documentation on board & valid. Name on both sides, forward part of hull, name & hailing port on stern, ≥ 4 " letters, contrasting color. Official number permanently marked on main beam. | O Yes O No O N/A | |
| 46 CFR 28.165 | Injury Placard: Required on all vessels. | O Yes O No O N/A | |
| 33 CFR 155.450 | Oil Pollution Placard: Required on all vessels ≥ 26 '. | O Yes O No O N/A | |
| 33 CFR 151.59 | MARPOL (Garbage) Placard: Required on all vessels ≥ 26'. | O Yes O No O N/A | |
| 33 USC 1602 33 USC 2020 72 COLREGS | Navigation Lights: During darkness and/or in or near areas of restricted visibility Side Lights (112.5°), all around white light (if < 12m or 39.4') or Mast Head Light (225°) & Stern Light (135°). Fishing Lights: In a vertical line, one meter apart. Red over White (360°) all other than trawling; Green over White (360°) when trawling. | O Yes O No O N/A | |
| 33 USC 1602 33 USC 2020 72 COLREGS | Dayshapes: Two black cones, apex to apex (not required on trollers). | O Yes O No O N/A | |
| 33 USC 1602 33 USC 2020 72 COLREGS | Sound Producing Devices: Vessels < 12m: Some means of making an efficient sound signal. Vessels ≥ 12m: Whistle audible for ½ mile & 7.9" bell. | O Yes O No O N/A | |
| 46 CFR 28.210 | First Aid/CPR: If operating beyond the Boundary Line, requires first aid & CPR trained & certified persons on board (POB) as follows: > 3 POB, one each; >17 POB, two each; one POB holding both certifications is acceptable. Requires "suitable" first aid kit & first aid manual. | O Yes O No O N/A | |
| 46 CFR 28.225 | Navigation Publications: If operating beyond the Boundary Line, corrected marine charts of operating area, U.S. Coast Pilot, Coast Guard Light List, Tide & Tidal Current Tables & (if > 12m or 39.4') copy of Inland Navigation Rules. | O Yes O No O N/A | |
| 46 CFR 28.230 | Magnetic Compass/Compass Deviation Table: If operating beyond the Boundary Line, requires operable magnetic compass at operating station & a current compass deviation table. | O Yes O No O N/A | |
| 46 CFR 28.245 47 CFR 80 33 CFR 26.03 46 CFR 28.375 | Communication Equipment: If operating beyond the Boundary Line, requires a VHF-FM radiotelephone (156 – 162 MHz) at the operating station, capable of operating three hours off an emergency power supply. | O Yes O No O N/A | |
| 47 CFR 80.405 | FCC Ship Radio Station License: If operating beyond the Boundary Line, all documented vessels required to carry radio transmitting equipment are required to have on board a current FCC Ship Radio Station License. | O Yes O No O N/A | |
| 46 CFR 28.240 | General Alarm System: If operating beyond the Boundary Line and there is an accommodation or workspace not adjacent to the operating station, requires an audible general alarm system with contact maker at the operating station; flashing red light in workspaces where the audible alarm is hard to hear (engine room), & red-letter warning signs "Attention General Alarm – When Alarm Sounds, Go To Your Station" at each bell or light. Public address system may be used if it meets criteria. Test prior to operating vessel & weekly afterwards. | O Yes O No O N/A | |
| 46 CFR 28.250 | High Water Alarms: If \geq 36' & operating beyond the Boundary Line, requires a visible & audible alarm at operating station to indicate high water in normally unmanned or non-watertight spaces (engine room, lazarette, fish hold, etc.). | O Yes O No O N/A | |
| 46 CFR 28.265 | Emergency Instructions: If operating beyond the Boundary Line, requires written Emergency Instructions. Must be posted if \geq 4 POB, kept available if \leq 4 POB. | O Yes O No O N/A | |
| 46 CFR 28.270 | Instructions, Drills, & Safety Orientation: If operating beyond the Boundary Line, requires master or individual-in-charge ensure monthly drills & instructions given to each person on board by a trained drill conductor. There are ten Required Drills & Instructions. Before operating vessel, persons on board who have not had drills & instruction must receive a safety orientation. | O Yes O No O N/A | |

Commercial Fishing Vessel Safety Exam Checklist Documented Vessels < 40°, within Coastal Waters

| 46 CFR 28.235 | Anchors & Radar Reflectors: If operating beyond the Boundary Line, requires radar reflector if vessels lacks strong radar signature (usually fiberglass hull vessels). Requires adequate anchor & sufficient line/cable for operating area. | O Yes O No O N/A | |
|------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------|--|
| LIFESAVING | | | |
| 46 CFR 28.145 46 CFR 28.140 | Visual Distress Signals: 3 hand-held rocket-propelled parachute red flares plus six hand red flares plus three floating orange smoke distress signals. | O Yes O No O N/A | |
| 46 CFR 28.110 46 CFR 28.135 46 CFR 28.140 | Personal Flotation Devices (PFDs): If beyond Boundary Line, one immersion suit for each person on board. In all other waters, one Type I, II, III, V or immersion suit for each person on board. Need PFD light if beyond Boundary Line; PFD marked w/name of vessel/wearer & retroreflective tape (31 sq. in.) front & back, properly maintained & stowed readily accessible. | O Yes O No O N/A | |
| 46 CFR 28.115 46 CFR 28.135 | Ring Life Buoys: One 24" ring life buoy marked w/vessel name/number, four strips of retroreflective tape, 60' of floating line & stowed readily accessible. | O Yes O No O N/A | |
| 46 CFR 28.120 46 CFR 28.125 46 CFR 28.130 46 CFR 28.140 | Survival Craft: If < 36', none required for warm water operations if < 4 persons on board; if \geq 4 persons on board, buoyant apparatus required; in cold water operations, none required if < 4 persons on board, if \geq 4 persons on board, buoyant apparatus required. If \geq 36' & < 4 persons on board, buoyant apparatus required for both warm & cold water operations; if \geq 4 persons on board, life float required for warm water operation & inflatable buoyant apparatus required for cold water operations. Survival craft may be stowed to float free or kept readily accessible. Buoyant apparatus & life float marked w/vessel name, four strips of retroreflective tape, 100' painter & electric light. The Fifth District Survival Craft Exemption may be advantageous during cold water operations. | O Yes O No O N/A | |
| ENGINE ROOM/MISCELLANEOUS | | | |
| 46 CFR 28.155 46 CFR 28.160 46 CFR 25.30 | Portable Fire Extinguishing Equipment: Two B-I or one B-II fire extinguisher on board. Must be USCG, UL or FM approved; mounted in approved bracket; in good condition; must have pressure gauge or inspection record. | O Yes O No O N/A | |
| 46 CFR 25.35 | Flame Arrestor: If using gasoline as fuel only. | O Yes O No O N/A | |
| 46 CFR 25.40 | Ventilation: If using gasoline as fuel only. | O Yes O No O N/A | |
| 33 CFR 159.7 | Marine Sanitation Device: Type I, II or III; required only if there is an installed toilet on board; Type III must be equipped to discharge ashore only. | O Yes O No O N/A | |
| 33 CFR 155.330 | Non-Oceangoing Vessels Able To: Retain oily mix on board & discharge to a facility. | O Yes O No O N/A | |
| 46 CFR 28.215 | Guards for Exposed Hazards: If operating beyond the Boundary Line, requires suitable hand covers, guards, or railings in way of machinery (gearing, chain or belt drives, rotating shafts, etc.) that may injure personnel. Not to restrict access to fishing gear. | O Yes O No O N/A | |
| 46 CFR 28.255 | Bilge Pump, Piping & Dewatering Systems: If operating beyond the Boundary Line, requires bilge pumps & piping capable of dewatering any watertight space. | O Yes O No O N/A | |

To schedule a "no fault, no penalty" voluntary dockside examination, please contact one of these fishing vessel safety professionals:

In Maryland, call: In Virginia, call: In southern New Jersey, call: In North Carolina, call the Baltimore, MD Examiner at (410) 576-2634 the Norfolk, VA Examiner at (757) 668-5533 the Philadelphia, PA Examiner at (215) 271-4989 the Atlantic Beach, NC Examiner at (252) 247-4562